


16V TRIPLEX



DESCRIPTION	AM / FM	DAB	GNSS	ROD LENGTH (L) mm	ROD THREAD	ROD TYPE	BASE ANGLE (α)	IP	P/N BOX	MOQ
TRIPLEX	•	•	•	300	M5	Antinoise	65°	66	15-7677841	1

TECHNICAL SPECIFICATION	AM / FM	DAB	GNSS
FREQUENCY	525-1710 kHz / 87,5-108 MHz	174 - 240 MHz	1559 - 1610 MHz
CONNECTOR	FAKRA Male White	FAKRA Male Black	FAKRA Male Blue
CABLE TYPE	RG 174	RG 174	RG 174
CABLE LENGTH	200 mm	245 mm	245 mm
POWER SUPPLY	12 Volt dedicated		3 - 5 Volt phantom
CONSUMPTION	75 mA (± 10 mA)		27 mA (± 10 mA)
IMPEDANCE	50 Ω	50 Ω	50 Ω
GAIN	FM: 2,5 dBi (Peak)	13 dBi (Peak)	38 dBi
VSWR	AM: < 2,5:1 / FM: < 3,5:1	< 2,5:1	< 1,9:1
COACHWORK DRILLING	Square: 15 x 15 mm - Round: 19 mm		

NOTES

Extension cables not included in the package.