V1. 04/18



... connecting to the aftermarket

# CTSSK002.2

Skoda Steering Wheel Control Interface





**Vehicle Application** 

Skoda Octavia (12) 2008 - 2013 Skoda Superb 2008 - 2013 Skoda Fabia (5J) 2013 - 2014 Skoda Rapid 2012 - 2015 Skoda Yeti (5L) 2009 - 2014

**Key Features** 

Retains Steering Wheel Controls (if equipped)

- Retains OEM Phone Buttons (if equipped)
- Provides Speed Pulse, Park Brake, Reverse Gear and Illumination Feeds





The information provided in this document is subject to change without notice due to manufacturer changes and/or improvements to the product/s.

# **ABOUT THIS PRODUCT**

# CTSSK002.2

CAN-Bus Steering Wheel Control Interface for Skoda vehicles with Quadlock connector.

#### WIRING COLOUR CODES

it Rear Speaker + it Rear Speaker - Rear Speaker + Rear Speaker - it Front Speaker + it Front Speaker - Front Speaker +	Yellow Black Red Orange Pink Green Purple/White	Permanent 12V Ground Ignition 12V Illumination Speed Pulse Park Brake Reverse Gear
Front Speaker -	Purple/ while	Reverse Gear
	t Rear Speaker - Rear Speaker + Rear Speaker - t Front Speaker + t Front Speaker - Front Speaker +	Rear Speaker +RedRear Speaker -Oranget Front Speaker +Pinkt Front Speaker -GreenFront Speaker +Purple/White

# PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.** 

#### **TECHNICAL SUPPORT**

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.



#### FITTING GUIDE

1. Remove and disconnect the original head unit.

2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.



# www.connects2.com

# FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

# STEERING WHEEL CONTROL FUNCTIONALITY

Original Button	Function	
VOL +	Volume +	
VOL -	Volume -	
Right Arrow	Track +	
Left Arrow	Track -	
Mute Icon	Mute	
Phone Button	Pick Up (Short Press)	
Phone Button	Hang Up (Long Press)	